

INTERNATIONAL EQUIPMENT AND ACCESSORIES CATALOG



FETCO[®]

TRUSTED | RELIABLE | QUALITY

fetco.com

THE GLOBAL BRAND YOU CAN TRUST

Originally founded in 1987 in Glenview, Illinois USA, FETCO® burst onto the coffee scene with its first patent: the Gravity Flow Dispense Tube, which is a built-in-system that prevents lime build up. Ever since, FETCO® continues to develop revolutionary technologies focused on manufacturing the finest coffee and tea equipment for the commercial markets.



We are Driven to Innovation

Whether we develop new products or update existing lines, our drive has always been, and will always be, "Innovation". That is, researching and developing superior and more efficient technologies to be applied to coffee and tea brewing systems. Take for instance the Temperature on Demand (TOD) Technology. A revolutionary Hot Water Dispenser, which has the ability to program and dispense four different and instant temperatures of water. Or the Cascading Spray Dome in our XTS™ Extractor® Touchscreen Coffee Brewing System. It's an innovative spray head mechanism that doesn't rust, it's easy to clean, prevents injuries when cleaning, and above all it delivers the best uniformity of extraction in the filter coffee industry.

We are Driven to Innovation

FETCO® energy-efficient equipment is designed and built to deliver significant energy savings by utilizing energy-conscious materials and technologies. The energy efficiencies of our equipment come from several sources, like insulation material and design, patented electrical innovative technologies, as well as conscious use of materials and components. Recent results from tests conducted by an independent laboratory show that FETCO® energy-efficient equipment can save up to 61% on the XTS line, up to 63% on the Iced Tea Brewers, and up to 61% on the Hot Water Dispensers, in comparison to similar equipment in the market.



Devoted to a Perfect Extraction

Every time we develop a new product, we always focus on the fundamental brewing criteria that are crucial within the filter coffee industry to achieve the proper coffee brewing or tea steeping, such as:

Uniformity of Extraction



Correct Water Temperature



Control of Brew Time



So, since the early stage of product development we check if what we are developing meets these industry standards and as a result all of our innovations and technologies always provide better extraction in our brewer, longer serving temperatures in our dispensers, and more flexibility to dispense the correct water temperature when it's required. Since 1987, our team has been working hard to consistently deliver a superior energy-efficient product and we will keep innovating to serve better and fresher beverages.

World's Local Service

Our global partners are essentially an extension of our company. They represent FETCO®, sharing the same values and principals, and we put as much effort to train them as we do in house with our team members. Every distributor is authorized after a period of training on both sales and technical service and they are all able to provide world service to any local operator. FETCO® is represented internationally by our long-term partners in more than 40 countries, in Asia, Latin America, Europe, Middle East, and Africa. FETCO® is the global brand that you can trust, to provide you with energy-efficient and groundbreaking technologies in coffee and tea equipment that are reliable and affordable.



XTS™ SERIES COFFEE BREWERS



Perfect taste begins with a simple touch...




User-Friendly Touchscreen

Access all controls via an inviting touchscreen interface display that blends intuitive icons with dynamic time and volume data to provide instant visual feedback at any point during programming, diagnostics or the brew cycle.



Streamlined Programming, Diagnostics and Metrics

The Extractor® Touchscreen Operating System (ETOS) was engineered for quick and efficient navigation through set-up, programming, diagnostics and daily operational brewing modes.



Customizable Screens

Customize the start screen to tie your equipment and product offerings into a consistent brand message. You can also create and display individual recipe names for quick and easy access to your most used coffee blends.

Legendary Extractor® Control

Take your coffee to its peak level by unlocking the full freshness, aroma and flavor of your taste profile with the legendary EXTRACTOR® brewing technology.



Program each separately to ensure perfectly balanced batch, no matter how much coffee you need at once.




Program each separately to ensure perfectly balanced batch, no matter how much coffee you need at once.



Allows you to control the length of time water is in contact with the coffee before the brew cycle.



Redirects water directly into the dispenser, bypassing the coffee grounds in the brew basket to provide your custom water-to-coffee ratio.



Percent of brew volume water designated for bypass.



Manually set the time between the end of the brew cycle and the unlocking of the brew basket, for increased safety.

STANDARD FEATURES:

Touchscreen Interface

Plastic Brew Baskets (Except 60 Series)

Brew Basket Sensors

Brew Basket Locks (Except 30 Series)

Manual Hot Water Faucet

Step-Down Design Increases Head Pressure for More Consistent Water Flow

Dispenser Guide For Both 3.0L Airpots and 1.0 Gallon Dispensers Included

SD Card Interface

Interchangeable parts with V+™ line

Stainless Steel Finish

Mixed Material Construction



Revolutionary Cascading Spray Dome®

Exclusive to FETCO®! This unique, patented feature provides even saturation of the coffee bed for maximum flavor and aroma extraction. It resists lime build up which means fewer service calls and more time producing revenue.



Pulse Brew System

Delivers intermittent pulses of water to ensure even saturation of the coffee bed for enhanced extraction.

CBS-2131XTS 3.0 / 3.8 / 4.0 Liter Airpot Single Coffee Brewer

FEATURES & BENEFITS

- 3.0 liter / 3.8 liter / 4.0 liter size provides flexibility for small- to medium-sized operations.
- Extractor® technology allows you to precisely dial-in the profile of even the most complex coffee blend to unlock its full freshness, aroma and flavor.
- User-friendly touchscreen interface display allows for quick and easy access to brew controls to quickly begin the brewing process for up to 4 separate coffee recipes and/or batch sizes.
- The brewer's low profile and small footprint make it the perfect choice for areas in which service space is at a premium – breakrooms, cafeteria countertops, lobby coffee service, etc.
- Built for flexible and portable, vacuum-lined pump lever Airpot service.
- Pre-programmed for 3.0 Liter output with simple instructions to configure for 4.0 Liter operation.
- Ships with 2 sets of adjustable legs and offers the flexibility of accommodating heights of either 3.0 Liter Airpots or 4.0 Liter Airpots and servers.



SETUP OPTIONS

Comes with 2.5" legs for 4.0 Liter Airpot or Luxus® Server and 3.0L Airpot. 1.0" legs specifically for 3.0L Airpots. Sold separately.



ELECTRICAL CONFIGURATION

Configuration Code	Heater Configuration	Voltage	Phase	Wires	KW	Electrical Connection	Max Amp Draw	Liter/Hour
NORTH AMERICA								
E213153	1 x 1.5 kW	100-120	1	2+G	1.1-1.6	NEMA 5-15P⁽³⁾	10.9-13.0	14.8⁽¹⁾
E213151	1 x 2.3 kW	100-120	1	2+G	1.7-2.4	NEMA 5-20P⁽³⁾	16.5-19.7	22.0⁽¹⁾
E213157	1 x 3.0 kW	200-240	1	2+G	2.2-3.1	NEMA 6-15P⁽³⁾	10.9-13.0	36.7⁽¹⁾
UNIVERSAL NORTH AMERICAN VOLTAGE OPTION								
E213172	1 x 1.7 kW	120	1	2+G	1.8	NEMA 5-15P⁽³⁾	14.7	16.7⁽¹⁾
Optional⁽²⁾	2 x 1.7 kW	120/208-240	1	3+G	3.5	L1 / L2 / N+G	14.7	32.9⁽¹⁾
E213173	1 x 2.3 kW	120	1	2+G	2.4	NEMA 5-20P⁽³⁾	19.7	22.0⁽¹⁾
Optional⁽²⁾	2 x 2.3 kW	120/208-240	1	3+G	4.7	L1 / L2 / N+G	19.7	41.6⁽¹⁾
INTERNATIONAL								
E213155	1 x 2.3 kW	200-240	1	2+G	1.6-2.3	Hardwired	8.2-9.8	22.0⁽¹⁾
E213191	1 x 3.0 kW	200-240	1	2+G	3.1	Hardwired	10.8-12.9	29.1⁽¹⁾
JAPAN								
E213180	1 x 2.3 kW	100	1	2+G	1.7	Hardwired	16.7	14.0⁽¹⁾
E213181	1 x 2.3 kW	200	1	2+G	1.7	Hardwired	8.3	21.0⁽¹⁾
E213182	1 x 3.0 kW	200	1	2+G	2.2	Hardwired	10.8	28.0⁽¹⁾
CE								
E213169	1 x 2.3 kW	230	1	L / N / PE	2.2	Hardwired	9.6	22.0⁽¹⁾
E213167	1 x 3.0 kW	230	1	L / N / PE	2.8	Hardwired	12.4	29.1⁽¹⁾

(1) Based on standard factory settings: 5.5 minute brew time; 0% prewet; 93°C water. 3 liters per batch. (2) Sold with factory cord & plug for 120 Volt configuration. Optional user connection to a terminal block requiring L1, L2, N and ground to 120/208-240 VAC. No Airpot locator for this group. User selectable for optional, dual in-series heater configuration. (3) Sold with factory cord & plug.

WATER SPECIFICATION

Water Inlet	Water Pressure	Minimum Flow Rate
3/8" Male Flare Fitting	20-75 psig (138-517 kPa)	5.7 lpm

DIMENSIONS

Type	Height	Width	Depth	Weight	Filled Weight
3.0 LITER SETUP					
Product	66.7 cm	29.8 cm	51.8 cm	13.0 kg	25.0 kg
Shipping	76.2 cm	43.2 cm	55.9 cm	19.0 kg	–
4.0 LITER SETUP					
Product	70.5 cm	29.8 cm	51.8 cm	13.0 kg	25.0 kg
Shipping	76.2 cm	43.2 cm	55.9 cm	19.0 kg	–

ACCESSORIES

- 2 Station Airpot Rack with Drip Tray **A034**
- 3 Station Airpot Rack with Drip Tray **A035**
- Single Serving Station for L4S-10 (S4S-10-1) **A147**
- Twin Serving Station for L4S-10 (S4S-10-2) **A148**
- Triple Serving Station for L4S-10 (S4S-10-3) **A149**
- Airpot Hot Tea Infuser **A112**
- Drip Tray - Square **A137**
- 1 Clip for Stainless Steel brew Basket (4 Per Basket are Needed) **1009.00003.00**

BREW BASKET GUIDE




BREW BASKETS

- 13" x 5" Stainless Steel **B003218B1**
- 13" x 5" Stainless Steel Tea Basket with Green Handle **B003110G1**
- 13" x 5" Plastic with Brown Insert **B014218BN2**

COLORED BREW BASKET HANDLE INSERTS

- Blue **1023.00180.00**
- Red **1023.00190.00**
- Green **1023.00191.00**
- Orange **1023.00192.00**



PAPER COFFEE FILTERS

- 13" x 5" (500 / Case) **F002**

WATER FILTRATION SYSTEM*

Everpure® Filter System and Replacement Cartridges
BWT Bestmax Filter System and Replacement Cartridges
See Page 63

DISPENSER GUIDE



CBS-2132XTS 3.0 / 3.8 / 4.0 Liter Airpot Twin Coffee Brewer

FEATURES & BENEFITS

- 2 x 3.0 liter / 3.8 liter / 4.0 liter size provides flexibility for small- to medium-sized operations.
- Extractor® technology allows you to precisely dial-in the profile of even the most complex coffee blend to unlock its full freshness, aroma and flavor.
- User-friendly touchscreen interface display allows for quick and easy access to brew controls to quickly begin the brewing process for up to 8 separate coffee recipes and/or batch sizes.
- Twin station configuration provides the flexibility of brewing two different recipes or into two different types of dispensers at the same time - or both!
- Built for flexible and portable, vacuum-lined pump lever Airpot service.
- Pre-programmed for 3.0 Liter output with simple instructions to configure for 4.0 Liter operation.
- Ships with 2 sets of adjustable legs and offers the flexibility of accommodating heights of either 3.0 Liter Airpots or 4.0 Liter Airpots and servers.



SETUP OPTIONS

Comes with 2.5" legs for 4.0 Liter Airpot or Luxus® Server and 3.0L Airpot. 1.0" legs specifically for 3.0L Airpots. Sold separately.



ELECTRICAL CONFIGURATION

Configuration Code	Heater Configuration	Voltage	Phase	Wires	KW	Electrical Connection	Max Amp Draw	Liter/Hour
NORTH AMERICA & JAPAN								
E213251	2 x 2.3 kW	200-240	1	2+G	3.3-4.7	Hardwired	16.5-19.7	43.5 ⁽¹⁾
E213252	2 x 3.0 kW	200-240	1	2+G	4.2-6.1	Hardwired	21.3-25.5	53.0 ⁽¹⁾
INTERNATIONAL								
E213254	2 x 2.3 kW	200-240	1	2+G	3.3-4.7	Hardwired	16.5-19.7	43.5 ⁽¹⁾
E213291	2 x 3.0 kW	200-240	1	2+G	4.2-6.1	Hardwired	21.3-25.5	53.0 ⁽¹⁾
CE								
E213264	2 x 2.3 kW	230/400	2	2L / N / PE	4.3	Hardwired	9.6	42.0 ⁽¹⁾
E213262	2 x 3.0 kW	230/400	2	2L / N / PE	5.6	Hardwired	12.4	56.0 ⁽¹⁾
E213268	2 x 2.3 kW	230	1	L / N / PE	4.3	Hardwired	18.8	42.0 ⁽¹⁾
E213266	2 x 3.0 kW	230	1	L / N / PE	5.6	Hardwired	24.4	56.0 ⁽¹⁾

(1) Based on standard factory settings: 5.5 minute brew time; 0% prewet; 93°C water. 3 liters per batch.

WATER SPECIFICATION

Water Inlet	Water Pressure	Minimum Flow Rate
3/8" Male Flare Fitting	20-75 psig (138-517 kPa)	5.7 lpm

DIMENSIONS

Type	Height	Width	Depth	Weight	Filled Weight
3.0 LITER SETUP					
Product	66.7 cm	50.2 cm	51.8 cm	21.3 kg	41.7 kg
Shipping	76.2 cm	58.4 cm	63.5 cm	25.0 kg	–
4.0 LITER SETUP					
Product	70.5 cm	50.2 cm	51.8 cm	21.3 kg	41.7 kg
Shipping	76.2 cm	58.4 cm	63.5 cm	25.0 kg	–

ACCESSORIES

- 2 Station Airpot Rack with Drip Tray **A034**
- 3 Station Airpot Rack with Drip Tray **A035**
- Single Serving Station for L4S-10 (S4S-10-1) **A147**
- Twin Serving Station for L4S-10 (S4S-10-2) **A148**
- Triple Serving Station for L4S-10 (S4S-10-3) **A149**
- Airpot Hot Tea Infuser **A112**
- Drip Tray - Square **A137**
- 1 Clip for Stainless Steel brew Basket (4 Per Basket are Needed) **1009.00003.00**

BREW BASKET GUIDE




BREW BASKETS

- 13" x 5" Stainless Steel **B003218B1**
- 13" x 5" Stainless Steel Tea Basket with Green Handle **B003110G1**
- 13" x 5" Plastic with Brown Insert **B014218BN2**

COLORS BREW BASKET HANDLE INSERTS

- Blue **1023.00180.00**
- Red **1023.00190.00**
- Green **1023.00191.00**
- Orange **1023.00192.00**



PAPER COFFEE FILTERS

- 13" x 5" (500 / Case) **F002**

WATER FILTRATION SYSTEM

Everpure® Filter System and Replacement Cartridges
BWT Bestmax Filter System and Replacement Cartridges
See Page 63

DISPENSER GUIDE



CBS-2152XTS-2G 8.0 Liter Twin Coffee Brewer

FEATURES & BENEFITS

- 2 x 8.0 liter size meets the high-volume demands of large-sized operations.
- EXTRACTOR® technology allows you to precisely dial-in the profile of even the most complex coffee blend to unlock its full freshness, aroma and flavor.
- User-friendly touchscreen interface display allows for quick and easy access to brew controls to quickly begin the brewing process for up to 8 separate recipes and / or batch sizes.
- Twin station configuration provides the flexibility of brewing two different recipes or into two different types of dispensers at the same time – or both!
- Designed to brew directly into our best-selling Luxus® L4D series portable dispensers and L4S series servers (sold separately).



ELECTRICAL CONFIGURATION

Configuration Code	Heater Configuration	Voltage	Phase	Wires	KW	Electrical Connection	Max Amp Draw	Liter/Hour
NORTH AMERICA								
E215351	2 x 3.0 kW	208-240	1 ⁽²⁾	2+G	4.6-6.1	Hardwired	22.4-25.8	58.0 ⁽¹⁾
	3 x 3.0 kW	208-240	3	3+G	6.9-9.1	Hardwired	19.5-22.5	85.2 ⁽¹⁾
E215352	2 x 5.0 kW	208-240	1 ⁽²⁾	2+G	7.6-10.1	Hardwired	36.9-42.5	95.8 ⁽¹⁾
	3 x 5.0 kW	208-240	3	3+G	11.4-15.1	Hardwired	32.0-36.9	145.0 ⁽¹⁾
INTERNATIONAL								
E215390	3 x 3.0 kW	220-240/380-415	3	4+G	9.1	Hardwired	11.8-12.9	85.0 (1)
E215391	3 x 5.0 kW	220-240/380-415	3	4+G	15.1	Hardwired	19.5-21.4	145.0 ⁽¹⁾
E215392	2 x 3.0 kW	208-240	1	2+G	4.6-6.1	Hardwired	22.4-25.8	58.0 ⁽¹⁾
E215394	2 x 5.0 kW	208-240	1	2+G	7.6-10.1	Hardwired	36.9-42.5	97.0 ⁽¹⁾
E215396	3 x 4.0 kW	240/415	3	4+G	12.1	Hardwired	17.1	99.0-113.0 ⁽¹⁾
JAPAN								
E215380	3 x 3.0 kW	200	3	3+G	6.5	Hardwired	18.6	64.0 ⁽¹⁾
CE								
E215361	3 x 3.0 kW	230/400	3	3L / N / PE	8.6	Hardwired	12.4	85.0 ⁽¹⁾
E215362	3 x 5.0 kW	230/400	3	3L / N / PE	14.1	Hardwired	20.4	145.0 ⁽¹⁾

(1) Based on standard factory settings: 5.5 minute brew time; 0% prewet; 93°C water. 8.0 liters per batch. (2) 1 or 3 phase configuration is field selectable by user. Sold factory configured for single phase 2 wire plus ground.

WATER SPECIFICATION

Water Inlet	Water Pressure	Minimum Flow Rate
3/8" Male Flare Fitting	20-75 psig (138-517 kPa)	5.7 lpm

DIMENSIONS

Type	Height	Width	Depth	Weight	Filled Weight
Product	98.7 cm	55.2 cm	57.8 cm	37.2 kg	81.6 kg
Shipping	94.0 cm	55.9 cm	68.6 cm	43.5 kg	–

ACCESSORIES

- 9" Airtop Brewing Stand for 1.5 Gallon Brewers **A010**
- Identifier Plates for TPD-15, Acrylic **A069**
- Single Serving Station for L4S-15 (S4S-15/20-1) **A150**
- Twin Serving Station for L4S-15 (S4S-15/20-2) **A151**
- Triple Serving Station for L4S-15 (S4S-15/20-3) **A152**
- 1.0/1.5 Gallon Hot Tea Infuser **A113**
- Drip Tray - Square **A137**
- 1 Clip for Stainless Steel brew Basket (4 Per Basket are Needed) **1009.00003.00**

BREW BASKET GUIDE




BREW BASKETS

- 16" x 6" Stainless Steel with Black Handle **B001280B1**
- 16" x 6" Stainless Steel with Clips with Black Handle **B002280B1C**
- 16" x 6" Plastic with Brown Insert **B015280BN2**
- 16" x 6" Stainless Steel Tea Basket with Green Handle **B001110G1**

COLORLED BREW BASKET HANDLE INSERTS

- Blue **1023.00180.00**
- Red **1023.00190.00**
- Green **1023.00191.00**
- Orange **1023.00192.00**



PAPER COFFEE FILTERS

- 15" x 5.5" (500 / Case) **F001**

WATER FILTRATION SYSTEM

- Everpure® Filter System and Replacement Cartridges
- BWT Bestmax Filter System and Replacement Cartridges
- See Page 63

DISPENSER GUIDE



D453
8.0 Liter LUXUS® Thermal Server (L4S-20)
Use with S4S Serving Stations
See page 60

D450
8.0 Liter LUXUS® Thermal Dispenser (L4D-20)

Food Equipment Technologies Company
600 Rose Road, Lake Zurich, IL 60047-0429 USA

800.338.2699 (US & Canada) | 847.719.3001

info@fetco.com | orders@fetco.com | techsupport@fetco.com



FETCO®, LUXUS®, and EXTRACTOR® are registered trademarks of Food Equipment Technologies Company. Specifications are subject to change without notice.
©2019 Food Equipment Technologies Company. Printed in USA. # CA14072-INTL